

# **AS 504 - Technical Specifications**



# **Description**

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific enduser requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

#### **UM**

International Standard

#### Construction



# Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Туре	π
Tyre Size	4.00 - 16
LI/SS DRIVE WHEEL	66 A8
LI/SS FREE ROLLING	78 A8

### **Dimensions International Standard**

Ply Rating	4
Section Width (mm)	110
Overall Diameter (mm)	628
Static Loaded Radius (mm)	296
Rolling Circumference (mm)	1935
Rim Rec	3.00 D
Rim Alt	2.50 C
ECE	E11-106R-005193

# Load capacity (Kg)

km/h / bar	2.80
10 FR	595
25 FR	505
30 FR	475
40 FR	425
10 DW	420
25 DW	355
30 DW	335
40 DW	300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 4/12/2025 5:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..