



AT 110 - Data Sheet

Description

AT 110 is BKT's tire suitable for all-terrain applications with ATVs. Thanks to its extraordinary steering control, AT 110 is the ideal front axle tire for your vehicle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: ATV



SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 20 X 7 - 8	STANDARD	4	5.5 AT	6.0 AT	183	508	TL	
AT 21 X 8 - 9	STANDARD	4	6.5 AT	6.0 AT	204	541	TL	
AT 21 X 7 - 10	STANDARD	4	5.5 AT	6.0 AT	178	531	TL	
AT 22 X 8 - 10	STANDARD	4	6.5 AT	6.0 AT	204	548	TL	
AT 23 X 7 - 10	STANDARD	4	5.5 AT	6.0 AT	178	584	TL	E4-75R-0006334

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 6:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..