

AT 171 - Technical Specifications



Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: ATV • Mud Bogger Tractor

Version	STANDARD
Type	TL
Tyre Size	AT 28 X 9 - 14
LI/SS	77 A8 / 53 F

Dimensions US Standard

Usa code	94056866
Ply Rating	6
Section Width (inch)	8.1
Overall Diameter (inch)	28.1
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load capacity (lbs)

	mph / psi	20	15
25 MUD BOGGING		908	-
50 MUD BOGGING		454	-
25 CASUAL TRANSPORT		-	740
50 CASUL TRANSPORT		-	375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/4/2025 6:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..