

## AT 625 - Technical Specifications



### Description

The AT 625 tire is designed for backhoe loaders and compact loaders, excelling in all farming, digging, and loading operations. It's also an ideal choice for sugarcane harvesting, offering the reliability needed to keep you productive throughout the season. With its extra deep tread, the AT 625 ensures increased puncture resistance and durability, allowing you to tackle tough conditions with confidence. This tire delivers outstanding traction and stability, combined with enhanced cut and chip resistance, making it a durable and dependable partner for your agricultural tasks.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Harvester

Industrial: Backhoe Loader • Compact Loader

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 28
LI/SS	152 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	450
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	645
Rolling Circumference (mm)	4254
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.60
40	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/5/2025 3:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..