



AW 09 - Data Sheet



Description

AW 09 has been developed for soil tillage, hay harvesting and transport applications with implements, balers and trailers. It is ideal for modern farming both on and off the road. Its reinforced carcass ensures high load capacity and a longer service tire life. AW 09 has been designed with a special cut-and-chip-resistant compound that provides extraordinary stubble resistance.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer

| SIZE | Version | USACode | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|----------------------|----------|----------|-------------------|--------------------|---------|-------------|------|------|------|-------|------|----------------|
| 260/70 - 15.3 | STANDARD | 94037858 | 110 A8 | 122 A8 | 9.00 | | 10.6 | 29.6 | 13.2 | 86.9 | TL | E4-106R-000372 |
| 260/70 - 15.3 | STANDARD | 94037841 | 114 A8 | 126 A8 | 9.00 | | 10.6 | 29.6 | 13.2 | 86.9 | TL | E4-106R-000373 |
| 260/70 - 15.3 | STANDARD | 94037919 | 119 A8 | 131 A8 | 9.00 | | 10.6 | 29.6 | 13.2 | 86.9 | TL | E4-106R-000374 |
| 300/80 - 15.3 | STANDARD | 94037803 | 129 A8 | 141 A8 | 9.00 | | 11.6 | 33.9 | 14.8 | 99.2 | TL | E4-106R-000376 |
| 300/80 - 15.3 | STANDARD | 94037810 | 120 A8 | 132 A8 | 9.00 | | 11.6 | 33.9 | 14.8 | 99.2 | TL | E4-106R-000375 |
| 300/80 - 15.3 | STANDARD | 94037902 | 126 A8 | 138 A8 | 9.00 | | 11.6 | 33.9 | 14.8 | 99.2 | TL | E4-106R-000377 |
| 320/80 - 15.3 | STANDARD | 94037834 | 133 A8 | 145 A8 | 9.00 | | 12.2 | 35.5 | 15.4 | 103.9 | TL | E4-106R-000378 |
| 400/60 - 15.5 | STANDARD | 94038053 | 132 A8 | 145 A8 | | AG 13.00 | 15.9 | 34.4 | 15 | 100.8 | TL | E4-106R-000381 |
| 380/55 - 17 | STANDARD | 94038077 | 125 A8 | 138 A8 | 13.00 | | 15.4 | 33.5 | 14.8 | 98.1 | TL | E4-106R-000379 |
| 380/55 - 17 | STANDARD | 94038060 | 128 A8 | 141 A8 | 13.00 | | 15.4 | 33.5 | 14.8 | 98.1 | TL | E4-106R-000380 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/13/2025 2:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..