



AW 708 - Data Sheet

Description

AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer
Industrial: Trailer



| SIZE | Version | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|---------------|-------------------|--------------------|----|----------|---------|-----|------|-----|------|------|-----------------|
| 400/60 - 15.5 | HD | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E11-106R-004253 |
| 400/60 - 15.5 | SPECIAL | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TT | E11-106R-004255 |
| 400/60 - 15.5 | SPECIAL | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | |
| 400/60 - 15.5 | STANDARD | 136 A8 | 10 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E11-106R-003514 |
| 400/60 - 15.5 | STANDARD | 145 A8 | 14 | AG 13.00 | | 405 | 875 | 380 | 2564 | TT | E4-106R-002712 |
| 400/60 - 15.5 | STANDARD | 145 A8 | 14 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E4-106R-002712 |
| 400/60 - 15.5 | STANDARD | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | E4-106R-001543 |
| 400/60 - 15.5 | STUBBLE RESISTANT | 149 A8 | 18 | AG 13.00 | | 405 | 875 | 380 | 2564 | TL | |
| 19.0/45 - 17 | STANDARD | 138 A8 | 10 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E4-106R-002334 |
| 19.0/45 - 17 | STANDARD | 144 A8 | 14 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E4-106R-001883 |
| 19.0/45 - 17 | STANDARD | 148 A8 | 18 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E4-106R-002268 |
| 19.0/45 - 17 | STUBBLE RESISTANT | 152 A8 | 22 | 16.00 | | 470 | 866 | 380 | 2536 | TL | E11-106R-003636 |
| 500/50 - 17 | STANDARD | 140 A8 | 10 | 16.00 | | 500 | 945 | 416 | 2750 | TL | E4-106R-001884 |
| 500/50 - 17 | STANDARD | 149 A8 | 14 | 16.00 | | 500 | 945 | 416 | 2750 | TL | E4-106R-001813 |
| 500/50 - 17 | STANDARD | 152 A8 | 16 | 16.00 | | 500 | 945 | 416 | 2750 | TL | |
| 500/50 - 17 | STANDARD | 154 A8 | 18 | 16.00 | | 500 | 945 | 416 | 2750 | TL | E4-106R-002269 |
| 500/65 - 17 | STANDARD | 160 A8 | 18 | 16.0 | | 525 | 1080 | 462 | 3135 | TL | E11-106R-004549 |
| 520/50 - 17 | STANDARD | 162 A8 | | 16.00 | | 516 | 952 | 404 | 2777 | TL | E11-106R-005852 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 6:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..