



CON STAR - Data Sheet



Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Compact Loader • Telehandler
Industrial: Compact Loader • Telehandler

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
340/80 - 18 (12.5/80 - 18)	INDUSTRIAL	94051304	143 A8		11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	13.8	40	18.3	119.7	TL	E11-106R-003020
340/80 - 20 (12.5/80 - 20)	INDUSTRIAL	94051311	144 A8		11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	13.8	41.9	19.3	128.8	TL	E11-106R-003021
380/75 - 20 (14.5 - 20)	INDUSTRIAL	94051519	148 A8		W 12	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13	15.2	42.5	19.7	128.9	TL	E11-106R-003022
400/70 - 20 (16.0/70 - 20)	INDUSTRIAL	94043323	149 A8	16	13	12 SDC ; 13 SDC ; 14	15.9	42.5	19.7	130	TL	E11-106R-003024
400/70 - 20 (16.0/70 - 20)	INDUSTRIAL	94051823	156 A8		13	12 SDC ; 13 SDC ; 14	15.9	42.5	19.7	130	TL	E11-106R-003023
400/70 - 20 (16.0/70 - 20)	INDUSTRIAL	94075874	161 A8		13	12 SDC ; 13 SDC ; 14	15.9	42.5	19.5	122.3	TL	E11-106R-0010150
400/70 - 24 (16.0/70 - 24)	INDUSTRIAL	94051977	158 A8		13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	15.6	46.3	21.4	140	TL	E11-106R-003025
400/80 - 24 (15.5/80 - 24)	INDUSTRIAL	94040599	162 A8	20	DW 13	DW 12 ; DW 13 L ; DW 14 L	15.9	49.2	22.4	148.9	TL	E11-106R-003026
440/80 - 24 (17.0/80 - 24)	INDUSTRIAL	94042067	168 A8	22	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.9	51.8	24	156.9	TL	E11-106R-003027
460/70 - 24 (17.5L - 24)	INDUSTRIAL	94052424	159 A8		DW 15 L	DW 14 L ; DW 16 L	18.1	49.2	22.1	149	TL	E11-106R-003029
500/70 - 24 (19.5L - 24)	INDUSTRIAL	94051731	164 A8		DW 16 L	DW 15 L ; DW 18 L	19.9	51.2	22.8	154.6	TL	E11-106R-003031
480/80 - 26 (18.4 - 26)	INDUSTRIAL	94052813	160 A8		DW 15 L	DW 16 L	19.3	55.5	25.3	168.2	TL	E11-106R-003033
440/80 - 28 (16.9 - 28)	INDUSTRIAL	94051199	156 A8		DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.7	55.9	24.9	169.3	TL	E11-106R-003035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..