

## CRANE SPECIAL - Technical Specifications



### Description

CRANE SPECIAL is suitable for pick & carry cranes on rough terrains. The tire is made of a special compound which provides high stability and durability.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Mobile Crane

Version	STANDARD
Type	TL
Tyre Size	14.00 - 24

## Dimensions International Standard

Ply Rating	24
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	628
Rolling Circumference (mm)	4050
Rim Rec	10.00 W
TRA Code	E3

## Load capacity (Kg)

km/h / bar	5.75
50	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/18/2025 11:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..