

D 405 - Data Sheet



Description

D 405 is a road-oriented tire ideal for transport applications with trailers and light trucks. An excellent grip on the road along with regular wear turns into extra durability.

UM

US Standard

Construction



Machinery

Agriculture: Light Truck • Trailer

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
10.50 - 16	STANDARD	94043880	14	6.00 T		11.4	38.6	TT	
7.50 - 16	STANDARD	94030613	12	6.00 G	5.50 F	8.3	31.9	TT	
7.50 - 16	STANDARD	94032488	14	6.00 G	5.50 F	8.3	31.9	TT	E4-54R-0022811
7.50 - 16	STANDARD	94032495	16	6.00 G	5.50 F	8.3	31.9	TT	E4-54R-0022812
9.00 - 16	STANDARD	94038558	12	6.50 H	6.00 G	10	36.4	TT	E11-106R-004656

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..