



EARTHMAX CRUSHER HAUL - Data Sheet



Description

EARTHMAX CRUSHER HAUL is an All Steel radial tire designed for transport applications, both on and off the road, as well as mining operations. It features enhanced durability and mileage along with high load capacity thanks to the strong steel-belted construction and casing. The block-type tread pattern provides excellent traction. In addition, EARTHMAX CRUSHER HAUL ensures excellent riding comfort, less driving fatigue and superior handling.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: On/Off Truck

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
10.00 R 20	STANDARD	94070558	149/146 J	7.50	8.00	10.7	41.9	0	0	TT	25
11.00 R 20	STANDARD	94070565	152/149 J	8.00	8.50	11.4	43.4	0	0	TT	25
12.00 R 24	STANDARD	94075959	160/156 K	8.50	9.00	12.2	48.4	22.2	149	TT	26
12.00 R 24	STANDARD	94075966	160/156 K	8.50	9.00	12.2	48.4	22.2	149	TL	26

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 7:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..