

# EARTHMAX SR 22 - Technical Specifications



## Description

EARTHMAX SR 22 (G-2/L-2) is an **All Steel** radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Industrial: Dozer • Grader • Loader

OTR: Dozer • Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/182 A2

## Dimensions US Standard

Usa code	94052387
Overall Width (inch)	17.8
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	155.5
Rim Rec	14.00/1.5
Star Rating	**
TRA Code	E2/L2
Tread Depth	35

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76	80	83	87	91	94
30	9650	10200	10500	11000	11400	12000	--	--	--	--	--
5	--	--	--	--	--	16100	16500	17100	17600	18200	18700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/5/2025 2:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..