

EARTHMAX SR 23 - Technical Specifications

Description

EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.



UM

US Standard

Construction

 RADIAL

Machinery

OTR: Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	161 A8/186 A2

Dimensions US Standard

Usa code	94060603
Overall Width (inch)	21.1
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	26.3
Rolling Circumference (inch)	176.7
Rim Rec	17.00/2.0
Star Rating	*
TRA Code	G2/L2
Tread Depth	39

Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73
25	5360	6150	6950	7600	8550	9100	9650	10200	--	--	--	--	--
5	--	--	--	--	--	--	--	--	17600	18200	19300	19800	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 7:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..