

EARTHMAX SR 431 - Data Sheet



Description

EARTHMAX SR 431 (E-4) is an All Steel tire specially designed for rigid haul trucks operating in severe mining conditions (surface and underground mines). The non-directional tread pattern ensures excellent traction and stability. The tire features a strong All Steel casing and a special tread compound providing extraordinary cut and chip resistance as well as a long service life even in rocky, abrasive and harsh environments.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
16.00 R 25	CUT RESISTANT COMPOUND	94073597	E4	**	177 B	11.25/2.0		17.8	60.3	28.1	183	TL	57	114
16.00 R 25	CUT RESISTANT COMPOUND	94073603	E4	***	183 B	11.25/2.0		17.8	60.3	28.1	183	TL	57	114
18.00 R 25	CUT RESISTANT COMPOUND	94070794	SH4	****		13.00/2.5		20.5	65.4	29.9	198.4	TL	62	0
18.00 R 25	CUT RESISTANT COMPOUND	94060788	E4	**	185 B	13.00/2.5		20.5	65.4	29.9	198.4	TL	62	96

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/11/2025 12:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..