



EARTHMAX SR 55 - Data Sheet



Description

EARTHMAX SR 55 is an All Steel radial tire specially designed for loaders, dozers and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability and traction.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
12.00 R 24	CUT RESISTANT COMPOUND	94071463	L5S	**	175 A2	8.50/1.3	8.0,9.0	12	50.2	22.5	149.1	TT	73
12.00 R 24	CUT RESISTANT COMPOUND	94071470	L5S	**	175 A2	8.50/1.3	8.0,9.0	12	50.2	22.5	149.1	TL	73
17.5 R 25	CUT RESISTANT COMPOUND	94041015	L5S	**	182 A2	14.00/1.5		17.8	55.1	24.8	165.8	TL	86
17.5 R 25	CUT RESISTANT COMPOUND	94069941	L5S	***	188 A2	14.00/1.5		17.8	55.1	24.8	165.8	TL	86
18.00 R 25	CUT RESISTANT COMPOUND	94053629	L5S	**	204 A2	13.00/2.5		20.2	65.6	28.9	191	TL	108
20.5 R 25	CUT RESISTANT COMPOUND	94062348	L5S	**	193 A2	17.00/2.0		21.1	60.7	27.6	182.8	TL	93
26.5 R 25	CUT RESISTANT COMPOUND	94042128	L5S	**	209 A2	22.00/3.0		27.2	70.3	31.9	211.6	TL	120
26.5 R 25	CUT RESISTANT COMPOUND	94075263	L5S	***	214 A2	22.00/3.0		27.2	70.3	31.9	211.6	TL	120
29.5 R 25	CUT RESISTANT COMPOUND	94044160	L5S	**	216 A2	25.00/3.5		30.6	75.3	33.9	226.6	TL	131
29.5 R 29	CUT RESISTANT COMPOUND	94040193	L5S	**	218 A2	25.00/3.5	24.00/3.5, 26.00/3.5	30.5	79.1	35.9	238.1	TL	131
35/65 R 33	CUT RESISTANT COMPOUND	94070350	L5S	***	229 A2	28.00/3.5	--	35.4	81.3	36	243.1	TL	125
35/65 R 33	CUT RESISTANT COMPOUND	94061709	L5S	**	224 A2	28.00/3.5	--	35.4	81.3	36	243.1	TL	125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/4/2025 10:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..