

EARTHMAX SR LOADER - Technical Specifications



Description

EARTHMAX SR LOADER is an OTR tire designed for loading and dozing operations as well as for Articulated dump truck application. Its All Steel casing along with multi-layer steel belts and a unique tread compound provide exceptional resistance to snags and punctures resulting in an extended service life. EARTHMAX SR LOADER features a unique tread pattern providing top self-cleaning properties and excellent traction on several types of terrain.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

Dimensions US Standard

Usa code	94064250
TMPH	116
Overall Width (inch)	20.9
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	172.6
Rim Rec	17.00/2.0
Star Rating	**/*
TRA Code	E3/L3
Tread Depth	37

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	12800	13600	14300	14800	15200	16100
5	17600	18200	19300	19800	20900	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 7:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..