

FARM 2000 - Technical Specifications



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	120 A8
LI/SS FREE ROLLING	132 A8

Dimensions US Standard

Usa code	94034673
Section Width (inch)	11.8
Overall Diameter (inch)	35
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	102.7
Rim Rec	9.00
ECE	E11-106R-003517

Load capacity (lbs)

mph / psi	41
5 FR	6170
15 FR	5250
20 FR	4940
25 FR	4410
5 DW	4320
15 DW	3670
20 DW	3460
25 DW	3090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/4/2025 10:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..