

FL 639 - Technical Specifications



Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader

Version	STANDARD
Type	TL
Tyre Size	560/45 R 22.5
LI/SS	152 D/163 A8

Dimensions US Standard

Usa code	94034260
Section Width (inch)	21.4
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.1
Rolling Circumference (inch)	130
Rim Rec	AG 16.00
ECE	E4-106R-000627

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2290	2650	3000	3570	4210	4780	5360	6000	6570	7130
40	2510	2910	3300	3950	4620	5250	5950	6530	7210	7830
30	3040	3520	3990	4740	5600	6390	7140	7970	8730	9480
25	3440	3980	4520	5400	6350	7210	8100	9020	9890	10750
15	3970	4590	5200	6220	7300	8320	9330	10360	11390	12370
5	4510	5210	5920	7050	8320	9480	10630	11790	12960	14090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/11/2025 11:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..