



FL 639 - Data Sheet



Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
560/45 R 22.5	STANDARD	94034260	152 D/163 A8			AG 16.00		21.4	42.4	19.1	130	TL	E4-106R-000627
600/50 R 22.5	STANDARD	94063239	168 B/156 B	156 B	168 B	AG 20.00		24.1	46.1	20.5	141.4	TL	E11-106R-006478
600/50 R 22.5	STANDARD	94028153	159 D/170 A8			AG 20.00		24.1	46.1	20.9	139.4	TL	E4-106R-000802
710/40 R 22.5	STANDARD	94063246	170 B/158 B	158 B	170 B	AG 24.00		28.6	44.9	19.8	137.5	TL	E11-106R-006479
710/40 R 22.5	STANDARD	94041176	161 D/172 A8			AG 24.00		28.6	44.9	19.8	137.5	TL	E4-106R-000801
800/40 R 22.5	STANDARD	94513420	168D/178A8			AG 28.00		32.6	47.7	21.2	143.4	TL	E11-106R-0010830
850/40 R 26.5	STANDARD	94064779	173 D / 184 A8			AG 28.00		33.9	53.3	23.6	162.3	TL	E11-106R-006228

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 5:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..