

FLOTATION 648 - Technical Specifications



Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Spreader

Version	STANDARD
Type	TL
Tyre Size	800/45 - 26.5
LI/SS DRIVE WHEEL	164 A8/160 B
LI/SS FREE ROLLING	177 A8/173 B

Dimensions US Standard

Usa code	94006564
Ply Rating	16
Section Width (inch)	31.5
Overall Diameter (inch)	54.8
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	164.8
Rim Rec	AG 28.00
ECE	E4-106R-002280

Load capacity (lbs)

mph / psi	26	29	32
5 FR	20030	21310	22530
10 FR	18020	19180	20280
20 FR	16030	17050	18020
25 FR	14310	15220	16090
30 FR	12870	13700	14330
5 DW	13720	14590	15430
10 DW	12350	13140	13890
20 DW	10980	11680	12350
25 DW	9800	10430	11020
30 DW	8820	9380	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..