



FLOTATION RIB 774 - Data Sheet



Description

FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Harvester • Hay Harvester • Trailer

SIZE	Version	USACode	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/60 - 22.5	STANDARD	94006601	160 A8/156 B	12	AG 16.00		21.7	48.8	21.3	146.7	TL	E11-106R-005941
550/60 - 22.5	STANDARD	94006618	167 A8/163 B	16	AG 16.00		21.7	48.8	21.3	146.7	TL	E11-106R-005942
600/55 - 22.5	STANDARD	94006632	169 A8/166 B	16	AG 20.00		23.6	48.4	21.3	146.3	TL	E11-106R-005944
600/55 - 22.5	STANDARD	94006625	164 A8/160 B	12	AG 20.00		23.6	48.4	21.3	146.3	TL	E11-106R-005943

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..