

# **FORESTMAX - Data Sheet**



# **Description**

FORESTMAX is BKT's new radial tire for tractors, which has been mainly developed for forestry applications, but can also be employed for some specific farming operations such as soil milling and stone breaking.

Its multi-ply polyester casing and the reinforced sidewall are designed to withstand the harsh forestry operating conditions. In addition, the cut-and-chip-resistant tread compound and the steel-belted structure significantly minimize the risk of punctures in the woodland. The tire features a robust open shoulder providing best traction and top stability even on rugged and uneven terrains. The combination of tread resistance and the particular shoulder design stand for optimum self-cleaning properties along with a long tire life making FORESTMAX your ideal partner in the forest.

### **UM**

International Standard

#### Construction



**₩** RADIAL

## Machinery

Agriculture: Tractor

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
540/65R28	STEEL BELTED	149A8/146B	W 18 L		550	1413	649	4247	675	TL	E11-106R-008830
600/60R28	STEEL BELTED	152A8/149B	DW18L	DW20B	570	1431	655	4315	675	TL	E11-106R-0010523
650/65R38	STEEL BELTED	172A8/186A2	DW 20 B	DW21B; DW23B	645	1811	832	5467	875	TL	
650/65R38	STEEL BELTED	164A8/160B	DW 20 B	DW21B; DW23B	645	1811	832	5467	875	TL	E11-106R-008829

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 4/13/2025 3:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..