



## GF 304 - Data Sheet

### Description

GF 304 is suitable for golf applications with golf carts. GF 304 ensures best comfort and turf protection. GF 304 is also available as "aramid-belted" version to provide increased puncture resistance.



### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Golf Kart

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	ARAMID BELTED	4	7.00 I - 55 ; I - 70 ; I - 90		216	460	202	1334	TL	E11-106R-005218
18 X 8.50 - 8	STANDARD	4	7.00 I - 55 ; I - 70 ; I - 90		216	460	202	1334	TL	E11-106R-003442
18 X 8.50 - 8	STANDARD	6	7.00 I - 55 ; I - 70 ; I - 90		216	460	202	1334	TL	E11-106R-005197

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 5:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..