



LIFTMAX LM 81 - Data Sheet



Description

LIFTMAX LM 81 has been specifically designed and engineered for heavy forklift and terminal tractors. Its aggressive and robust tread pattern together with the unique Antistatic tread compound ensure excellent wear properties and a long service life.

The strong All Steel casing and the reinforced sidewall provide maximum stability and handling during lift mode, together with a superior traction. In addition, its radial casing absorbs surfaces irregularities to provide a better riding comfort and increase operator confidence.

LIFTMAX LM 81 is Antistatic compliant, and all its sizes are capable of dissipating static charge from the vehicle.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Hay Harvester

Industrial: Forklift

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	Type	ECE
150/75 R 8	STANDARD	94069316	113 A5	4.33R		5.9	16.9	TL	
150/75 R 8 IMP	STANDARD	94075423	109 A8	4.33R		5.9	16.9	TL	E11-106R-009051
180/70 R 8	STANDARD	94063642	125 A5	4.33R		6.7	17.8	TL	
180/70 R 8 IMP (18X7 R 8)	STANDARD	94067596	120 A8	4.33R		6.7	17.8	TL	E11-106R-006913
5.00 R 8	STANDARD	94059423	111 A5	3.00D	3.25 I; 3.75 I	5.4	18.5	TL	
200/75 R 9	STANDARD	94069200	134 A5	6.00E		8	20.9	TL	
6.00 R 9	STANDARD	94048878	121 A5	4.00E		6.3	21.3	TL	
225/75 R 10	STANDARD	94060467	142 A5	6.50F		8.7	23.4	TL	
6.50 R 10	STANDARD	94048885	128 A5	5.00F	5.50F	7	23.2	TL	
250/75 R 12	STANDARD	94051724	152 A5	8.0		10.2	26.8	TL	
7.00 R 12	STANDARD	94044979	136 A5	5.00S		7.7	26.6	TL	
225/75 R 15 (28 X 9 R 15)	STANDARD	94052967	149 A5	7.00		8.9	28	TL	
250/70 R 15	STANDARD	94062904	153 A5	7.00		9.1	28.9	TL	
315/70 R 15	STANDARD	94067657	165 A5	8.00		12	32.8	TL	
7.00 R 15	STANDARD	94052820	143 A5	5.50	5.00	7.8	29.3	TL	
7.50 R 15	STANDARD	94048847	146 A5	6.00	6.5	8.3	30.6	TL	
8.25 R 15	STANDARD	94052950	153 A5	6.5	7.0	9.2	32.9	TL	
10.00 R 20	STANDARD	94049004	166 A5	7.50		10.8	42	TL	
11.00 R 20	STANDARD	94053728	170 A5	8.00	8.5	11.3	43	TL	
12.00 R 20	INDUSTRIAL	94070534	176 A5	8.50	8.0	12.4	44.6	TL	
12.00 R 20	STANDARD	94053025	176 A5	8.50	8.0	12.4	44.6	TL	
9.00 R 20	STANDARD	94073177	160 A5	7.0	7.5	10	40.5	TL	
12.00 R 24	STANDARD	94056989	178 A5	8.50	9.0	12.2	48.6	TT	
12.00 R 24	STANDARD	94069668	178 A5	8.5	9.0	12.2	48.6	TL	
14.00 R 24	INDUSTRIAL	94070541	193 A5	10.00W	10.0, 10.00WA	15.3	55.7	TL	
14.00 R 24	STANDARD	94058549	193 A5	10.00W	10.0, 10.00WA	15.3	55.7	TL	
16.00 R 25	STANDARD	94069071	200 A5	11.25/2.0	13.00/2.0	17.3	60.2	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 12:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..