

## LUG STAR - Data Sheet



### Description

LUG STAR is an industrial tire designed for road-rail excavator applications where exceptional traction is required. It features excellent self-cleaning properties and a very resistant tread compound. The robust casing provides excellent durability.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Road Rail Equipment

SIZE	Version	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
10.00 - 20	STANDARD	14	7.5	7.0 ; 8.0	280	1080	506	3343	TT
10.00 - 20	STANDARD	18	7.5	7.0 ; 8.0	280	1080	506	3343	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/19/2025 6:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..