

MINE STAR XL - Technical Specifications



Description

MINE STAR XL is a bias-ply tire particularly suitable for load haul dumps (LHD) in underground loading and hauling operations. The wide tread design with open lugs avoids stone trapping and provides exceptional traction. The larger footprint makes MINE STAR XL your best ally for heavy-duty underground mining operations. MINE STAR XL is made of a special tread compound that ensures extraordinary cut and chip resistance, providing increased operational efficiency as well as an extended tire life-cycle and reduced machine downtime.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Load Haul Dump (LHD)

Version	STANDARD
Type	TL
Tyre Size	55 X 20.00 - 34

Dimensions International Standard

Ply Rating	44
Section Width (mm)	485
Overall Diameter (mm)	1365
Rim Rec	16.00
TRA Code	L5
Tread Depth	61

Load capacity (Kg)

km/h / bar	10.00
5	18755
10	16600
15	15435
25	14115

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 7:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..