

MULTIMAX MP 525 - Technical Specifications



Description

MULTIMAX MP 525 is an All-Steel multi-purpose radial tire designed for universal vehicle, telehandlers, compact loaders, and graders in agro-industrial applications. The tire has been specifically developed to carry heavy loads at higher speeds both on and off the road. Indeed, the large non-directional tread design provides exceptional traction on any surface in addition to excellent self-cleaning properties. The strong sidewall ensures exceptional lateral stability in lift mode, making it the ideal choice for agricultural and material handling operations. MULTIMAX MP 525 is made of a unique, cut- and-chip-resistant tread compound that stands for a longer tire service life thanks to its extraordinary resistance against any kinds of cuts and punctures.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Telehandler • Universal Vehicle

Industrial: Compact Loader • Grader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	405/70 R 18 (15.5/70 R 18)
LI/SS	146 J/141 B/153 A2

Dimensions International Standard

Overall Width (mm)	405
Overall Diameter (mm)	1025
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3122
Rim Rec	13
Rim Alt	11; 12
ECE	E11-54R-0022030

Load capacity (Kg)

km/h / bar	3.75	4.00
100	2800	3000
50	2575	-
10	3650	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 12:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..