

PAC MASTER - Technical Specifications



Description

PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Compactor

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 16

Dimensions US Standard

Usa code	94002467
Ply Rating	6
Section Width (inch)	10.8
Overall Diameter (inch)	31.9
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	97.6
Rim Rec	8.0
ECE	E11-106R-005274

Load capacity (lbs)

mph / psi	65
5	4080
10	3310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 7:39 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..