

PAC MASTER - Technical Specifications



Description

PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Compactor

Version	SPECIAL
Type	TT
Tyre Size	11.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	291
Overall Diameter (mm)	1070
Static Loaded Radius (mm)	494
Rolling Circumference (mm)	3310
Rim Rec	8.0
Rim Alt	8.5
ECE	E11-106R-003407

Load capacity (Kg)

	km/h / bar	7.25
	10	5450
	15	4375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 7:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..