

PRO RIB F2M - Technical Specifications



Description

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: 2WD Tractor
Industrial: Trailer

| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 9.5L - 15 SL |
| LI/SS | 102 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94020492 |
| Ply Rating | 8 |
| Section Width (inch) | 9.4 |
| Overall Diameter (inch) | 30.7 |
| Static Loaded Radius (inch) | 14.3 |
| Rolling Circumference (inch) | 91.5 |
| Rim Rec | 7.00 |
| Rim Alt | 8 LB |
| ECE | E4-106R-002644 |
| TRA Code | F2M |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 48 |
| 25 | 1870 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/8/2025 4:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..