



RIB 774 (B) - Data Sheet

Description

RIB 774 (B) is a low-section implement tire. It is ideal for modern farming and suitable for on- and off-the-road applications with implement machinery and trailers. It features great load capacity and a long tire life-cycle. An "HD" version is available for heavy-duty services.



UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Trailer
Industrial: Trailer

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
15.0/55 - 17	STANDARD	141 A8	14	13.00	13	391	850	377	2490	TL	E11-106R-004311
15.0/55 - 17	STANDARD	134 A8	10	13.00	13	391	850	377	2490	TL	E11-106R-004309

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 6:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..