



SIERRA MAX - Data Sheet



Description

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: ATV

SIZE	Version	Star R	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
AT 25 X 10 R 12	STANDARD	***	50 N	8.0		260	640	294	1923	TL	E11-75R-005087
AT 25 X 8 R 12	STANDARD	***	43 N	6.5		206	640	292	1899	TL	E11-75R-005088
AT 26 X 11 R 14	STANDARD	***	54 N	9.00		280	675	310	2027	TL	E11-75R-005096
AT 26 X 9 R 14	STANDARD	***	48 N	7.00		230	675	307	2005	TL	E11-75R-005095
AT 27 X 11 R 14	STANDARD	***	56 N	9.00		280	700	318	2091	TL	E11-75R-005097
AT 27 X 9 R 14	STANDARD	***	50 N	7.00		230	700	316	2070	TL	E11-75R-005099

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 6:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..