

SIERRA MAX - Data Sheet



Description

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

UM

US Standard

Construction



Machinery

Agriculture: ATV

SIZE	Version	USACode	Star R	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Туре	ECE
AT 25 X 10 R 12	STANDARD	94064793	***	50 N	8.0		10.2	25.2	11.6	75.7	TL	E11-75R-005087
AT 25 X 8 R 12	STANDARD	94064786	***	43 N	6.5		8.1	25.2	11.5	74.8	TL	E11-75R-005088
AT 26 X 11 R 14	STANDARD	94052332	***	54 N	9.00		11	26.6	12.2	79.8	TL	E11-75R-005096
AT 26 X 9 R 14	STANDARD	94052325	***	48 N	7.00		9.1	26.6	12.1	78.9	TL	E11-75R-005095
AT 27 X 11 R 14	STANDARD	94052622	***	56 N	9.00		11	27.6	12.5	82.3	TL	E11-75R-005097
AT 27 X 9 R 14	STANDARD	94052615	***	50 N	7.00		9.1	27.6	12.4	81.5	TL	E11-75R-005099

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 6:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..