

SURE TRAX HD - Technical Specifications

Description

SURE TRAX HD is a block pattern tire for skid steers in construction applications. It shows excellent cut and chip resistance as well as top rim protection. SURE TRAX HD is ideal for paved surfaces and heavy-duty service.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer



Version	INDUSTRIAL
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	151 A2

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	855
Rim Rec	13.00
ECE	E11-106R-006012

Load capacity (Kg)

	km/h / bar	4.80
	10	3450
	15	2725
	25	2520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/4/2025 11:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..