

# TERRA TRAX - Technical Specifications

## Description

TERRA TRAX has been specially designed for fodder and feeder implement. It is best suited for both on-and-off-the-road usage. TERRA TRAX shows excellent road performance, driving comfort and self-cleaning features. The low rolling resistance contributes to better fuel economy.

## UM

International Standard

## Construction

 BIAS

## Machinery

Agriculture: Implement Machinery



Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5
LI/SS	156 A8

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	395
<b>Overall Diameter (mm)</b>	785
<b>Static Loaded Radius (mm)</b>	361
<b>Rolling Circumference (mm)</b>	2370
<b>Rim Rec</b>	14.00
<b>ECE</b>	E11-106R-006002

## Load capacity (Kg)

<b>km/h / bar</b>	<b>6.00</b>
<b>40</b>	<b>4000</b>

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 7:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..