



## TF 8181 - Data Sheet

### Description

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: 2WD Tractor  
Industrial: Trailer



SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.00 - 15	STANDARD	F2	66 A6	4	3.00 D	4 J	112	605	287	1834	TT	E11-106R-005191
5.00 - 15	SPECIAL	F2	82 A6	6	4.00 E	3.00 D ; 4 J ; 4½ J	142	655	307	1951	TT	E11-106R-005213
5.00 - 15	STANDARD	F2	73 A6	4	4.00 E	3.00 D ; 4 J ; 4½ J	142	655	307	1951	TT	
5.00 - 15	STANDARD	F2	82 A6	6	4.00 E	3.00 D ; 4 J ; 4½ J	142	655	307	1951	TT	E4-106R-001951
10.00 - 16	STANDARD	F2	115 A6	8	W 8	W 8 L	273	895	411	2667	TT	E4-106R-002672
11.00 - 16	STANDARD	F2	118 A6	8	W 10 L	W 8 ; W 8 L	326	970	447	2920	TT	E4-106R-002673
4.00 - 16	STANDARD	F2	69 A6	4	3.00 D		112	630	301	1877	TT	E4-106R-002183
4.50 - 16	STANDARD	F2	73 A6	4	3.00 D		122	655	311	1952	TT	E4-106R-001953
5.00 - 16	SPECIAL	F2	84 A6	6	4.00 E	3.00 D ; 4 J ; 4½ J	140	680	322	2025	TT	E11-106R-004090
5.00 - 16	STANDARD	F2	76 A6	4	4.00 E	3.00 D ; 4 J ; 4½ J	140	680	322	2025	TT	
5.00 - 16	STANDARD	F2	84 A6	6	4.00 E	3.00 D ; 4 J ; 4½ J	140	680	322	2025	TT	E4-106R-001954
5.50 - 16	SPECIAL	F2	86 A6	6	4.00 E	3.50 D ; 4.50 E	158	720	340	2145	TT	
5.50 - 16	STANDARD	F2	86 A6	6	4.00 E	3.50 D ; 4.50 E	158	720	340	2145	TT	E4-106R-001955
6.00 - 16	SPECIAL	F2	88 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F	173	745	350	2220	TT	E11-106R-004410
6.00 - 16	SPECIAL	F2	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	173	745	350	2220	TT	E11-106R-004415
6.00 - 16	STANDARD	F2	88 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F	173	745	350	2220	TT	E4-106R-001959
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	173	745	350	2220	TT	E4-106R-002186
6.50 - 16	HD	F2	98 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	180	770	361	2295	TT	E11-106R-005227
6.50 - 16	SPECIAL	F2	102 A6	10	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	180	770	361	2295	TT	E4-106R-002707
6.50 - 16	SPECIAL	F2	91 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	180	770	361	2295	TT	
6.50 - 16	STANDARD	F2	91 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	180	770	361	2295	TT	E4-106R-001960
7.50 - 16	IMPLEMENT	F2	122 A6	14	5.50 F	5.00 F ; 5 K ; 6.00 F	205	820	383	2445	TT	E4-106R-002670
7.50 - 16	SPECIAL	F2	98 A6	6	5.50 F	5.00 F ; 5 K ; 6.00 F	205	820	383	2445	TT	E11-106R-004412
7.50 - 16	SPECIAL	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	205	820	383	2445	TT	E11-106R-004413
7.50 - 16	STANDARD	F2	98 A6	6	5.50 F	5.00 F ; 5 K ; 6.00 F	205	820	383	2445	TT	E4-106R-002634
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	205	820	383	2445	TT	E4-106R-002709
7.50 - 16	STANDARD	F2	109 A6	10	5.50 F	5.00 F ; 5 K ; 6.00 F	205	820	383	2445	TT	E4-106R-002708
9.00 - 16	STANDARD	F2	111 A6	8	6.00 F	5.50 F ; 6.50 F	234	855			TT	E11-106R-0010326
6.00 - 18	STANDARD	F2	101 A6	8	4.50 E	4.00 E ; 5.00 F	172	800	374	2410	TT	E11-106R-005253
7.50 - 18	HD	F2	106 A6	8	5.50 F		208	875	410	2605	TT	E11-106R-005254
7.50 - 18	SPECIAL	F2	101 A6	6	5.50 F		208	875	410	2605	TT	
7.50 - 18	SPECIAL	F2	106 A6	8	5.50 F		208	875	410	2605	TT	E11-106R-005254
7.50 - 18	STANDARD	F2	101 A6	6	5.50 F		208	875	410	2605	TT	E4-106R-002639
7.50 - 18	STANDARD	F2	106 A6	8	5.50 F		208	875	410	2605	TT	E4-106R-002645
6.00 - 19	STANDARD	F2	93 A6	6	4.50 E	4.00 E ; 5.00 F	174	830	385	2425	TT	E4-106R-001963
6.50 - 20	SPECIAL	F2	101 A6	8	5.00 F	4.00 E ; 5.50 F	180	865	409	2578	TT	
6.50 - 20	STANDARD	F2	97 A6	6	5.00 F	4.00 E ; 5.50 F	180	865	409	2578	TT	E4-106R-001964
6.50 - 20	STANDARD	F2	101 A6	8	5.00 F	4.00 E ; 5.50 F	180	865	409	2578	TT	E4-106R-002833
7.50 - 20	HD	F2	103 A6	6	5.50 F	5.00 F	205	915	431	2725	TT	
7.50 - 20	HD	F2	109 A6	8	5.50 F	5.00 F	205	915	431	2725	TT	E11-106R-004314
7.50 - 20	SPECIAL	F2	109 A6	8	5.50 F	5.00 F	205	915	431	2725	TT	E11-106R-005255
7.50 - 20	STANDARD	F2	103 A6	6	5.50 F	5.00 F	205	915	431	2725	TT	E4-106R-002635
7.50 - 20	STANDARD	F2	109 A6	8	5.50 F	5.00 F	205	915	431	2725	TT	E4-106R-002710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/11/2025 11:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..