

TR 126 - Data Sheet



Description

TR 126 is designed to fit small tractors in soil tillage operations. The deep lugs and the tread pattern provide excellent traction and outstanding load capacity features providing best tire performance in all operating conditions.

UM

International Standard

Construction

Machinery Agriculture: Small Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	sw	OD	SLR	RC	Туре	ECE
6 - 14	HD	R1	80 A6	8	5 JA ; 5 KB		157	655	305	1978	TT	E11-106R-007418
6 - 14	STANDARD	R1	66 A6	4	5 JA ; 5 KB		157	655	305	1978	TL	E11-106R-003476
6 - 14	STANDARD	R1	66 A6	4	5 JA ; 5 KB		157	655	305	1978	TT	E11-106R-003476
7 - 14	STANDARD	R1	95 A6	8	5 JA ; 5 KB		170	690	320	2070	TT	E11-106R-005233
7 - 14	STANDARD	R1	72 A6	4	5 JA ; 5 KB		170	690	320	2070	TL	E11-106R-003356
7 - 14	STANDARD	R1	72 A6	4	5 JA ; 5 KB		170	690	320	2070	TT	E11-106R-003356

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 12:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..