

## TR 135 - Technical Specifications



### Description

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor  
Industrial: Trailer

Version	STANDARD
Type	TT
Tyre Size	9.5 - 32
LI/SS	110 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	235
Overall Diameter (mm)	1255
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3686
Rim Rec	W 8
Rim Alt	W 7
ECE	E4-106R-002033
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.10
30	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/7/2025 1:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..