



## TR 137 - Data Sheet

### Description

TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version provides extraordinary cut and chip resistance, and an extended tire life-cycle.



### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Harvester

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
24.5 - 32	STANDARD	R1	159 A6	12	DW 21 B	DW 20 B	622	1805	807	5343	825	TL	E4-106R-002271
24.5 - 32	STANDARD	R1	163 A6	14	DW 21 B	DW 20 B	622	1805	807	5343	825	TL	E4-106R-002273
30.5L - 32	ARAMID BELTED	R1	170 A6	18	DH 27 B	DW 27 B	770	1865	831	5520		TL	E4-106R-002271
30.5L - 32	HD	R1	170 A6	18	DH 27 B	DW 27 B	770	1865	831	5520		TL	E4-106R-002283
30.5L - 32	STANDARD	R1	162 A6	12	DH 27 B	DW 27 B	770	1865	831	5520		TL	E4-106R-002274
30.5L - 32	STANDARD	R1	164 A6	14	DH 27 B	DW 27 B	770	1865	831	5520		TL	
30.5L - 32	STANDARD	R1	167 A6	16	DH 27 B	DW 27 B	770	1865	831	5520		TL	E4-106R-002282

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..