

## TR 171 - Data Sheet



### Description

TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Designed with a special compound, TR 171 provides excellent traction and extraordinary durability also in the harshest operating conditions.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
5.00 - 12	STANDARD	R1W+	61 A6	4	3.00 D DT ; 3.00 D	4 JA ; 3.50 B	130	580	272	1750		TT		E11-106R-003358
5.00 - 12	STANDARD	R1W+	67 A6	6	3.00 D DT ; 3.00 D	4 JA ; 3.50 B	130	580	272	1750		TT		E11-106R-003486
6.00 - 12	STANDARD	R1W+	76 A6	6	4.00 E DT ; 4.00 E	4 JA	160	635	298	1953		TT		E11-106R-003487
9.5 - 16	STANDARD	R1W+	96 A6	6	W 8 L	8 LB	241	845	395	2607		TT		E11-106R-003497
8 - 18	STANDARD	R1W+	100 A6	8	W 6	W 7 ; 5.50 F	190	845	391	2617		TT	1	E11-106R-006170
8 - 18	STANDARD	R1W+	85 A6	4	W 6	W 7 ; 5.50 F	190	845	391	2617		TT		E11-106R-003488
8 - 18	STANDARD	R1W+	94 A6	6	W 6	W 7 ; 5.50 F	190	845	391	2579		TT		E11-106R-002960
9.5 - 18	STANDARD	R1W+	105 A6	8	W 8		241	900	423	2790		TT		E11-106R-003552
11.2 - 20	STANDARD	R1W+	113 A6	8	W 10	W 9 ; 9	285	1005	471	3101		TT	0	E11-106R-003506
14.9 - 28	STANDARD	R1W+	130 A6	8	W 13	W 11 ; W 12	388	1370	636	4246	650	TT		E11-106R-003585
8.3 - 20	HD	R1W+	96 A6	6	W 7	W 6	210	900	422	2788		TT	1	E11-106R-004089
8.3 - 20	HD	R1W+	101 A6	8	W 7	W 6	210	900	424	2785		TT		E11-106R-007208
8.3 - 20	STANDARD	R1W+	96 A6	6	W 7	W 6	210	900	423	2704		TT		E11-106R-003362
8.3 - 20	STANDARD	R1W+	101 A6	8	W 7	W 6	210	900	422	2806		TT		E11-106R-004329
9.5 - 20	HD	R1W+	107 A6	8	W 8	W 7	241	955	449	2942		TT	1	E11-106R-004105
9.5 - 20	STANDARD	R1W+	107 A6	8	W 8	W 7	241	955	449	2942		TT		E11-106R-004105
9.5 - 20	STANDARD	R1W+	101 A6	6	W 8	W 7	241	955	449	2942		TT		E11-106R-003359
8.3 - 22	STANDARD	R1W+	104 A6	8	W 7	W 6	205	945	444	2778		TT		E11-106R-003489
9.5 - 22	STANDARD	R1W+	110 A6	8	W 8	W 7	244	1005	472	3107		TT		E11-106R-003490
11.2 - 24	STANDARD	R1W+	120 A6	10	W 10	W 9	285	1105	517	3403	525	TT		E11-106R-004478
11.2 - 24	STANDARD	R1W+	110 A6	6	W 10	W 9	285	1105	519	3388	525	TT		E11-106R-003492
11.2 - 24	STANDARD	R1W+	116 A6	8	W 10	W 9	285	1105	517	3403	525	TT	0	E11-106R-004098
12.4 - 24	HD	R1W+	120 A6	8	W 11	W 9 ; W 10	315	1165	544	3557	550	TT	0	E11-106R-004117
12.4 - 24	STANDARD	R1W+	106 A6	4	W 11	W 9 ; W 10	315	1165	544	3557	550	TT		E11-106R-004479
12.4 - 24	STANDARD	R1W+	115 A6	6	W 11	W 9 ; W 10	315	1165	544	3557	550	TT		E11-106R-004480
12.4 - 24	STANDARD	R1W+	120 A6	8	W 11	W 9 ; W 10	315	1165	544	3557	550	TT		E4-106R-002741
13.6 - 24	STANDARD	R1W+	119 A6	6	W 12	W 11	355	1210	562	3674		TT		E11-106R-003553
13.6 - 24	STANDARD	R1W+	123 A6	8	W 12	W 11	355	1210	562	3674		TT	0	E11-106R-004110
14.9 - 24	STANDARD	R1W+	123 A6	6	W 13	W 11 ; W 12	391	1265	575	3792	600	TT		E11-106R-003377
14.9 - 24	STANDARD	R1W+	128 A6	8	W 13	W 11 ; W 12	391	1265	575	3792	600	TT		E4-106R-002742
8.3 - 24	HD	R1W+	105 A6	8	W 7	W 6	210	1005	474	3153		TT		E11-106R-005249
8.3 - 24	STANDARD	R1W+	100 A6	6	W 7	W 6	210	1005	474	3014		TT		E11-106R-003491
8.3 - 24	STANDARD	R1W+	105 A6	8	W 7	W 6	210	1005	474	3153		TT		E11-106R-004477
9.5 - 24	STANDARD	R1W+	106 A6	6	W 8	W 7	240	1066	500	3260		TT		E4-106R-002031
9.5 - 24	STANDARD	R1W+	111 A6	8	W 8	W 7	240	1066	496	3263		TT	0	E11-106R-004099
11.2 - 26	STANDARD	R1W+	117 A6	8	W 10	W 9	284	1155	540	3396		TT		E11-106R-003554
12.4 - 26	STANDARD	R1W+	121 A6	8	W 11	W 10 ; W 9	315	1210	573	3727		TT		E11-106R-003666
13.6 - 26	HD	R1W+	135 A6	12	W 12	W 11	340	1270	589	3774		TT		
13.6 - 26	STANDARD	R1W+	110 A6	4	W 12	W 11	340	1270	580	3774		TT		
13.6 - 26	STANDARD	R1W+	120 A6	6	W 12	W 11	340	1270	582	3815		TT		E11-106R-003555
13.6 - 26	STANDARD	R1W+	126 A6	8	W 12	W 11	340	1270	587	3835		TT	1	E11-106R-004481
12.4 - 28	STANDARD	R1W+	117 A6	6	W 11	W 9 ; W 10	315	1260	589	3860	600	TT		E11-106R-003556
12.4 - 28	STANDARD	R1W+	123 A6	8	W 11	W 9 ; W 10	315	1260	589	3860	600	TT		E11-106R-004496
12.4 - 28	STANDARD	R1W+	131 A6	12	W 11	W 9 ; W 10	315	1260	589	3860	600	TT		E11-106R-004497

13.6 - 28	HD	R1W+	125 A6	8	W 12	W 11	350	1325	616	4007	TT	0	E11-106R-004111	
13.6 - 28	HD	R1W+	134 A6	12	W 12	W 11	350	1325	614	4013	TT	1	E11-106R-004112	
13.6 - 28	STANDARD	R1W+	112 A6	4	W 12	W 11	350	1325	614	4013	625	TT		
13.6 - 28	STANDARD	R1W+	121 A6	6	W 12	W 11	350	1325	614	4013	625	TT	E11-106R-003584	
13.6 - 28	STANDARD	R1W+	125 A6	8	W 12	W 11	350	1325	614	4013	625	TT	E11-106R-003011	
13.6 - 28	STANDARD	R1W+	134 A6	12	W 12	W 11	350	1325	614	4013	625	TT	0	E11-106R-004112
14.9 - 28	HD	R1W+	137 A6	12	W 13	W 11 ; W 12	388	1370	636	4246	650	TT	E11-106R-004115	
14.9 - 28	HD	R1W+	130 A6	8	W 13	W 11 ; W 12	388	1370	635	4176	650	TT	E11-106R-003585	
14.9 - 28	STANDARD	R1W+	137 A6	12	W 13	W 11 ; W 12	388	1370	636	4246	650	TT	E11-106R-004498	
16.9 - 28	STANDARD	R1W+	135 A6	8	W 15 L	W 14 L	435	1440	674	4496	675	TT	E11-106R-003586	
16.9 - 28	STANDARD	R1W+	143 A6	12	W 15 L	W 14 L	435	1440	674	4496	675	TT	E11-106R-003385	
14.9 - 30	STANDARD	R1W+	131 A6	8	W 13	W 11 ; W 12	380	1415	658	4282	675	TT	E11-106R-003587	
16.9 - 30	STANDARD	R1W+	137 A6	8	W 15 L	W 14 L	430	1490	687	4535	700	TT	E11-106R-003588	
16.9 - 30	STANDARD	R1W+	143 A6	12	W 15 L	W 14 L	430	1490	687	4605	700	TT	0	E11-106R-004113
18.4 - 30	STANDARD	R1W+	145 A6	10	W 16 L	W 15 L	470	1550	710	4706	725	TT	E11-106R-003589	
12.4 - 32	STANDARD	R1W+	124 A6	8	W 11	W 9 ; W 10	315	1370	643	4232	650	TT	E11-106R-003386	
16.9 - 34	STANDARD	R1W+	139 A6	8	W 15 L	W 14 L	429	1585	736	4838	750	TT	E11-106R-003590	
18.4 - 34	STANDARD	R1W+	146 A6	10	W 16 L	W 15 L	470	1655	768	4866	775	TT	E11-106R-003591	
12.4 - 36	STANDARD	R1W+	126 A6	8	W 11	W 9 ; W 10	315	1470	691	4332	700	TT	E11-106R-003592	
13.6 - 36	STANDARD	R1W+	129 A6	8	W 12	W 11	345	1520	717	4647	725	TT	E11-106R-003593	
13.6 - 38	STANDARD	R1W+	131 A6	8	W 12	W 11	345	1565	729	4818	750	TT	E4-106R-002750	
16.9 - 38	STANDARD	R1W+	141 A6	8	W 15 L	W 14 L	429	1685	788	4954	800	TT	E11-106R-003594	
18.4 - 38	STANDARD	R1W+	148 A6	10	W 16 L	W 15 L	470	1760	815	5364	825	TT	E11-106R-003387	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 4:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..