



TR 270 - Data Sheet



Description

TR 270 is a tractor tire suitable for soil tillage applications. It is specially designed for providing maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning features. TR 270 perfectly meets all these characteristics.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
23.1 - 26	STANDARD	94004898	R2	141 A8	8	DW 20 A ; DW 20 B		23.2	64.8	29.1	193.8	TT	0	
23.1 - 26	STANDARD	94027958	R2	145 A8	10	DW 20 A ; DW 20 B		23.2	64.8	29.1	193.8	TT	0	E11-106R-003620
23.1 - 26	STANDARD	94028580	R2	149 A8	12	DW 20 A ; DW 20 B		23.2	64.8	29.1	193.8	TT	0	E11-106R-004499
23.1 - 26	STANDARD	94038503	R2	149 A8	12	DW 20 A ; DW 20 B		23.2	64.8	29.1	193.8	TL	0	E11-106R-004499
23.1 - 26	STANDARD	94029211	R2	152 A6	14	DW 20 A ; DW 20 B		23.2	64.8	29.1	193.8	TT	0	E11-106R-003617
18.4 - 30	STANDARD	94004829	R2	135 A8	8	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	18.3	62.2	28.3	188.5	TT	0	E11-106R-003557
18.4 - 30	STANDARD	94038398	R2	135 A8	8	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	18.3	62.2	28.3	188.5	TL	0	E11-106R-003557
18.4 - 30	STANDARD	94032907	R2	145 A8	12	DW 16 L ; DW 16 A	W 15 L ; DW 15 A	18.3	62.2	28.3	188.5	TT	0	E11-106R-004121
23.1 - 30	STANDARD	94004911	R2	143 A8	8	DW 20 A ; DW 20 B		23.2	68.8	31.1	205.8	TT	0	
23.1 - 30	STANDARD	94027965	R2	147 A8	10	DW 20 A ; DW 20 B		23.2	68.8	31.1	205.8	TT	0	E11-106R-003622
23.1 - 30	STANDARD	94026500	R2	151 A8	12	DW 20 A ; DW 20 B		23.2	68.8	31.1	205.8	TT	0	E11-106R-004504
18.4 - 34	STANDARD	94004843	R2	137 A8	8	DW 16 A ; W 16 L	W 15 L	18.3	66.2	30.4	198	TT	0	E11-106R-003558
18.4 - 34	STANDARD	94028573	R2	146 A8	12	DW 16 A ; W 16 L	W 15 L	18.3	66.2	30.4	198	TT	1	E11-106R-004517
23.1 - 34	STANDARD	94004935	R2	145 A8	8	DW 20 A ; DW 20 B		23.2	72.8	33.1	217.8	TT	0	
23.1 - 34	STANDARD	94027972	R2	150 A8	10	DW 20 A ; DW 20 B		23.2	72.8	33.1	217.8	TT	0	E11-106R-003623
23.1 - 34	STANDARD	94030897	R2	152 A8	12	DW 20 A ; DW 20 B		23.2	72.8	33.1	217.8	TT	0	E11-106R-004507
23.1 - 34	STANDARD	94031030	R2	156 A8	14	DW 20 A ; DW 20 B		23.2	72.8	33.1	217.8	TT	0	E11-106R-004510
13.6 - 38	STANDARD	94051069	R2	119 A8	6	W12	DW12A , W11	13.6	63	0	190.1	TT	0	E11-106R-004340
18.4 - 38	STANDARD	94004867	R2	139 A8	8	W 16 A ; W 16 L	W 15 L ; DD 16	18.3	70.2	32.4	210	TT	0	E11-106R-003559
18.4 - 38	STANDARD	94038947	R2	149 A8	12	W 16 A ; W 16 L	W 15 L ; DD 16	18.3	70.2	32.4	210	TT	0	E11-106R-004511
20.8 - 38	STANDARD	94004874	R2	144 A8	8	W 18 A ; W 18 L	DD 18 ; DW 18 A	20.9	73.8	33.9	224.2	TT	0	E11-106R-003378
20.8 - 38	STANDARD	94026531	R2	148 A8	10	W 18 A ; W 18 L	DD 18 ; DW 18 A	20.9	73.8	33.9	224.2	TT	0	E11-106R-004512
20.8 - 38	STANDARD	94038954	R2	152 A8	12	W 18 A ; W 18 L	DD 18 ; DW 18 A	20.9	73.8	33.9	224.2	TT	0	E11-106R-004513
13.6 - 46	STANDARD	94050826	R2	122 A8	6	W12	W12A	13.6	71	0	214.2	TT	0	E11-106R-004343

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 12:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without

prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..