

TR 387 - Technical Specifications



Description

TR 387 is an agro-industrial tire suitable for sugar cane trailers and compactors. It features high load capacity and is available in different versions to meet specific user requirements in terms of cut and chip resistance, heavyduty services and durability. The "dual bead" version is particularly suitable for industrial tractors and transport operations using trailers.

UM

US Standard

Construction



Machinery

Agriculture: Trailer Industrial: Compactor

Version	HD
Туре	TL
Tyre Size	18.4 - 26
LI/SS	148 A8

Dimensions US Standard

Usa code	94034086
Ply Rating	16
Section Width (inch)	19.1
Overall Diameter (inch)	57.1
Static Loaded Radius (inch)	25
Rolling Circumference (inch)	163.4
Rim Rec	DW 16 L
Rim Alt	DW 15 L
TRA Code	R3

Load capacity (lbs)

mph / psi	42
25	6950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 12:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..