



## TR 390 - Data Sheet

### Description

TR 390 is an agro-industrial tire suitable for sugar cane trailers and compactors. TR 390 features high load capacity and increased durability. Its "dual bead HD" version is particularly suitable for industrial tractors and transport operations using trailers, whereas its "dual bead HD special" version is ideal for heavy-duty service.



### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Industrial: Compactor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
23.1 - 26	DUAL BEAD HD	R3	161 A6	18	DW 20 B		595	1560	690	4545	750	TL	E11-106R-004607
23.1 - 26	HD DUAL BEAD SPECIAL	R3	161 A6	18	DW 20 B		595	1560	690	4545	750	TL	E11-106R-004629
23.1 - 26	STANDARD	R3	145 A6	8	DW 20 B		595	1560	690	4545	750	TL	E11-106R-003595
23.1 - 26	STANDARD	R3	153 A6	12	DW 20 B		595	1560	690	4545	750	TL	E4-106R-002317
23.1 - 26	STANDARD	R3	159 A6	16	DW 20 B		595	1560	690	4545	750	TL	E11-106R-004606
28L - 26	DUAL BEAD	R3	160 A6	16	DW 25 B	DW 23 B	714	1560	690	4545		TL	E4-106R-002337
28L - 26	DUAL BEAD HD	R3	172 A6	20	DW 25 B	DW 23 B	714	1560	690	4545		TL	E11-106R-004609
28L - 26	STANDARD	R3	154 A6	12	DW 25 B	DW 23 B	714	1560	690	4545		TL	E11-106R-004608

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 12:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..