

## TR 459 - Technical Specifications



### Description

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Backhoe Loader • Tractor  
Industrial: Backhoe Loader

Version	INDUSTRIAL
Type	TL
Tyre Size	19.5L - 24
LI/SS	151 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	490
Overall Diameter (mm)	1333
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	4031
Rim Rec	DW 16 L
ECE	E4-106R-002300
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.30
40	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 6:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..