



## TRAC FARM PLUS - Data Sheet



### Description

TRAC FARM PLUS is a rear tractor tire specifically designed for soil tillage and haulage applications. The tire features a deeper tread with dual angle lugs to ensure both excellent traction and a comfortable ride on the road. The special tread design provides more contact for better stability and great self-cleaning properties. TRAC FARM PLUS ensures a longer tire life-cycle.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.4 - 28	STANDARD	94045419	R1	121 A8	12	W 11	W 9 ; W 10	12.6	51	23.7	153.5	TT	E11-106R-004526
13.6 - 28	STANDARD	94045686	R1	124 A8	12	W 12	W 11	14.4	53	24.4	160.9	TT	E11-106R-004527
14.9 - 28	STANDARD	94057436	R1	130 A8	12	W 13	W 12 ; W 11	15.4	54.3	25.3	164.5	TT	E11-106R-006811
16.9 - 28	STANDARD	94045143	R1	139 A8	12	W 15 L	W 14 L	17.3	56.5	26	169.2	TT	E11-106R-003627
16.9 - 30	STANDARD	94046119	R1	140 A8	12	W 15 L	W 14 L	17.3	58.1	26.7	175.8	TT	E11-106R-004529

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/12/2025 5:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..