

## XL GRIP (BHL) - Technical Specifications



### Description

XL GRIP has been specially designed for backhoe loaders that are employed in heavy-duty operations in excavation, dozing and loading applications. The non-directional tread pattern provides best traction and stability. The special tread compound results in excellent cut and chip resistance and an extended tread life.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Backhoe Loader

Version	STANDARD
Type	TT
Tyre Size	12.5/80 - 18
LI/SS FREE ROLLING	148 A8

## Dimensions US Standard

Usa code	94051533
Ply Rating	16
Section Width (inch)	12
Overall Diameter (inch)	38.6
Rim Rec	W 9
Rim Alt	11

## Load capacity (lbs)

mph / psi	71
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/4/2025 10:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..