

## XL GRIP (G3) - Technical Specifications



### Description

XL GRIP (G-3) is a bias-ply tire for graders designed to minimize cuts and punctures in heavy-duty grading environments where exceptional traction is required.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Grader

Version	STANDARD
Type	TL
Tyre Size	16.00 - 24 (-)

## Dimensions US Standard

Usa code	94044276
Ply Rating	16
Overall Width (inch)	17
Overall Diameter (inch)	57.1
Static Loaded Radius (inch)	25.7
Rolling Circumference (inch)	168.9
Rim Rec	10.00 VA SDC
Rim Alt	-
TRA Code	G3
Tread Depth	41

## Load capacity (lbs)

mph / psi	44
25	9900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/10/2025 10:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..