

XL GRIP ULTRA - Data Sheet



Description

XL GRIP ULTRA is a bias-ply tire, particularly suitable for on/off trucks in heavy-duty service conditions such as mining applications, quarries and construction sites. The non-directional tread design provides excellent front and lateral traction. The tire features a strong nylon casing with optimized tie bars and a special tread compound to ensure high cut and puncture resistance as well as excellent durability and wear resistance in addition to best self-cleaning properties even on rocky surfaces.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: On/Off Truck

SIZE	Version	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
10.00 - 20	STANDARD	18	7.5	7.0	285	1075	505	3257	TT	22
11.00 - 20	STANDARD	18	8.0	7.5	297	1115	529	3368	TT	24
12.00 - 20	CUT RESISTANT	20	8.5	8.0	320	1155	545	3465	TT	24
12.00 - 20	STANDARD	20	8.5	8.0	320	1155	545	3465	TT	24
12.00 - 24	CUT RESISTANT	20	8.5	8.0	320	1250	585	3710	TT	24
12.00 - 24	INDUSTRIAL	24	8.5	8.0	320	1250	585	3710	TT	24
12.00 - 24	STANDARD	20	8.5	8.0	320	1250	585	3710	TT	24

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/28/2025 4:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..