

FARM 2000 - Specificații tehnice



Descriere

Anvelopa FARM 2000 este potrivită pe tractoare pentru aplicații de prelucrare a solului. A fost proiectată cu un compus special rezistent la tăiere și așchiere pentru a asigura o durabilitate mai bună. Datorită carcasei sale puternice, FARM 2000 oferă o capacitate mare de încărcare. De asemenea, oferă proprietăți excelente de tracțiune și auto-curățare.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Tractor

Versiune	SPECIAL
Tip	TT
Dimensiunea anvelopei	12.4 - 28
LI/SS	122 A8

Dimensiuni US Standard

Usa code	94063871
Rating de sarcină	12
Lățimea secțiunii (inch)	12.6
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	156.3
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-005965
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	3300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 2/5/2025 3:31 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..