

COMMANDER 3 RIB - Технические спецификации



Description

COMMANDER 3 RIB — это передние шины с трехреберным рисунком протектора, разработанные для обработки почвы и грузоперевозок. Благодаря оптимизированному распределению нагрузки на ребра в центре и на боковинах они обеспечивают превосходную прочность и грузоподъемность. Прочный каркас и протектор из устойчивой к порезам и разрывам резиновой смеси гарантирует невероятную стойкость к проколам.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор 2WD

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	212
Overall Diameter (mm)	810
Rim Rec	5.50 F
Rim Alt	5.00 F ; 5 K ; 6.00 F
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	875

Printed on 27.07.2024 13:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..