

## AGRIMAX RT 955 - Tekniska specifikationer



### Description

AGRIMAX RT 955 är ett radialdäck från BKT avsett för arbete med radgrödor. Vissa storlekar lämpar sig även för besprutning och vingårdar. Det speciella däkmönstret med rundad däcksuldra ger utmärkt dragförmåga med hög prestanda, stabilitet och själrensande egenskaper. Tack vare det robusta däckhöljet har AGRIMAX RT 955 hög lastkapacitet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Besprutningsbil • Skördemaskin för vingård

Version	STANDARD
Type	TL
Tyre Size	300/95 R 46 (12.4 R 46)
LI/SS	148D/151A8

## Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	1738
Static Loaded Radius (mm)	812
Rolling Circumference (mm)	5318
SRI (mm)	825
Rim Rec	W 9
Rim Alt	W 10 ; W 11 ; DW 10 ; DW 11
ECE	E11-106R-0010269
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1105	1295	1670	2020	2240	2365	2585	2805	2995	3150
50	1160	1360	1755	2120	2355	2485	2715	2950	3145	3310
40	1210	1415	1830	2210	2450	2590	2830	3075	3280	3450
30	1270	1490	1925	2320	2575	2720	2975	3230	3445	3625
10	1655	1940	2505	3025	3355	3545	3875	4210	4490	4725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/22/2024 4:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..